

# ALS 333 C - ALS 433 C - ALS 453 C

## Airless Pumps



ALS 333 C







ALS 433 C



ALS 453 C



Model	ALS 333 C	ALS 433 C	ALS 453 C
 Max working fluid pressure bar	6.8 bar		
 Pressure ratio n:n	25:1	30:1	53:1
 Max fluid output l/min	2.4 l/min	4.7 l/min	2.8 l/min
Max fluid pressure	170 bar	204 bar	360 bar
Fluid output per cycle	~26 ml/cycle	~59 ml/cycle	~35 ml/cycle
Max cycle	92 cycles/min	80 cycles/min	
Cycle Srtocke	58 mm	93 mm	
Required air compressor	> 0.75 kW	> 1.5 kW	
Max working temperature	5 ~ 40° C		
Noise level (LAeqT)*	84.1 dB (A)*	78.1 dB (A)*	78.6 dB (A)*
Airless spray gun	manual = ALG 7 / automatic = AL 96		
Plunger pump type	PP1251 C	PP4301 C	PP4531 C
Dimensions (mm)	500x500x900	500x500x970	
 Weight g	23 Kg	30 Kg	
Air hose connection	G 1/4"		
Fluid hose connection	G 1/4"		
Paint Filter	TF 8	TF 9	
Suction Filter	50 Mesh		

\*This noise level is measured according to machine directive 89/392 and ISO 3744.

CE  II 2G T6 X

declaration of ATEX conformity for use in zone 1 and in zone 2