

TOF-50 (Flat Pattern) & TOF-50R (Round Pattern)

COMPACT MOLD RELEASE AGENT SPRAY GUN

With compact, light weight and wide tulip pattern.
The gun features easy handling at a narrow space
and short distance spraying.

- Easy handling due to locating air and liquid joints at bottom of grip
- Less tiring design due to compact and light
- From the background that more waterborne release agent has been used:
 - Corrosion-proof: Body is made of forged aluminum + alumite treatment for corrosion-proof.
 - Many parts fixed on body are made of stainless steel for rust prevention.
 - Vaseline is used as grease on slide parts in air pass.
 - Body is treated with pearskin (sandy) finish for slippery release agent.
- Max. flow rate 180 ml/min, nozzle orifice size 0.6 mm
- Fluid adjusting and pattern adjusting knobs have a locking mechanism
- Option: Gun hook (w/2 bolts) Code No 93018920 Gun hook can be fixed on top of gun or side of grip Using it gun can be hung on worker's belt etc.



MODEL	 Ø mm	 No.	 bar	 ml/min	 l/min	 mm
-------	--	---	---	--	---	--


TOF-50 FLAT PATTERN

TOF-50-022P	0.2	E2	1.0	20	50	120
TOF-50-032P	0.3			50		140
TOF-50-042P	0.4			130		150
TOF-50-062P	0.6			180		
TOF-50-082P	0.8			220		
TOF-50-102P	1.0			280		
TOF-50-122P	1.2	350	230			
TOF-50-142P	1.4	E4		1.5	500	65

TOF-50R ROUND PATTERN

TOF-50R-022P	0.2	1	0.5	20	20	40
TOF-50R-032P	0.3		1.0	50	30	
TOF-50R-042P	0.4		1.5	130	70	
TOF-50R-062P	0.6		2.0	180		40
TOF-50R-082P	0.8		2.5	220		50
TOF-50R-102P	1.0		3.5	280		55
TOF-50R-122P	1.2	2	3.5	350	80	
TOF-50R-142P	1.4		500	75		

Connection hose: • Outside ø 6 mm • Inside ø 4 mm



declaration of ATEX conformity for use in zone 1 and in zone 2